



**FILTER  
TECHNOLOGY**

cleaner fluids mean better business



Filtration and Contamination Control Specialists

## FM40325D Bypass Filtration Unit

Designed to suit CAT® differential and final drive lube system



### Function

For permanent on-board filtration of the differential and final drive system.

### Features

- Fitted with a pressure compensating flow control regulator on the inlet to the filters.
- Filter system operating pressure 3.1 – 3.5 bar (45 – 50 psi).
- 5 bar check valve to protect the filters from pressure spikes.
- Pressure gauge to indicate filter housing pressure.
- Suitable for systems up to 800 litres (215 gallons).
- Live sample point.

### Filters

- 3 x FM3202 industrial filter housing.

### Mounting

- Heavy duty powder coated frame.

### Flow

- 4.5 litre/min (1.2 gal/min).

### FM40325 Dimensions

	Metric	US
Height	650 mm	25.6"
Width	600 mm	23.6"
Depth	300 mm	11.8"
Weight	35 kg	77.1 lb
Max Pressure	5 bar	72 psi
Recommended operating pressure	3.5 bar	51 psi



Filter Technology Australia

Office: 44 Bonville Avenue, Thornton NSW 2322 • Postal: PO Box 101 Beresfield NSW 2322

Tel: +61 2 4966 1833 • Fax: +61 2 4966 1933 • Toll Free Australia: 1800 626 899

Email: info@filtertechnology.com.au • Web: www.filtertechnology.com.au

