




**FILTER
TECHNOLOGY**

cleaner fluids mean better business



Filtration and Contamination Control Specialists

FM40445 Hydraulic Bypass Filtration Unit

Designed to suit large hydraulic systems on face shovels and excavators



Function

For on-board filtration of large hydraulic systems on face shovels and excavators.

Features

- Fitted with a pressure compensating flow control regulator on the inlet to the filters.
- Filter system operating pressure 3.1 – 3.5 bar (45 – 50 psi).
- 5 bar check valve to protect the filters from pressure spikes.
- Pressure gauge to indicate filter housing pressure.
- Suitable for systems up to 6500 litres (1717 gallons).
- Live sample point.
- Ball valve that enables you to isolate the unit.
- Non-Return Valve on Outlet

Filters

- 4 x FM3204 industrial filter housing.

Mounting

- Heavy duty powder coated frame.

Flow

- 16 – 18 litre/min (4.2 – 4.7 gal/min).

FM40445 Dimensions

	Metric	US
Height	1050 mm	41.3"
Width	840 mm	33.1"
Depth	600 mm	23.6"
Weight	70kg	154.3 lb
Max Pressure	5 bar	72 psi
Recommended operating pressure	3.5 bar	51 psi



Filter Technology Australia

Office: 44 Bonville Avenue, Thornton NSW 2322 • Postal: PO Box 101 Beresfield NSW 2322

Tel: +61 2 4966 1833 • Fax: +61 2 4966 1933 • Toll Free Australia: 1800 626 899

Email: info@filtertechnology.com.au • Web: www.filtertechnology.com.au

